

SPECIFICATIONS



| A CONTRACTOR OF THE CONTRACTOR | PP8516T2 | PP8520T2* | PP8524T2* |
|--|--------------------------|--------------------------|--------------------------|
| Body: Length Width | 17' 6" 8' 4" | 21' 6" 8' 4" | 25' 6" 8' 4" |
| Length Overall: Width Height | 19' 8" 8' 6" 8' 2" | 23' 8" 8' 6" 8' 2" | 27' 8" 8' 6" 8' 2" |
| Length Interior: Width Height | 17' 3" 8' 1" 6' 6" | 21' 3" 8' 1" 6' 6" | 25' 3" 8' 1" 6' 6" |
| Width Between Wheel Wells | 83" | 83" | 83" |
| Platform Height | 19" | 19" | 19" |
| Spring Suspension E-Z Lube® Axles: Qty Total Axle Capacity | Tandem 7,000 lbs. | Tandem 7,000 lbs. | Tandem 7,000 lbs. |
| Electric Brakes with Breakaway Kit | Electric Drum | Electric Drum | Electric Drum |
| Radial Tire Size Tire Load Range | ST205/75R15 C | ST205/75R15 C | ST205/75R15 C |
| Hitch Ball Size | 2-5/16″ | 2-5/16" | 2-5/16″ |
| Hitch Height to Top of Ball | 18" | 18" | 18" |
| Hitch Weight (% of Curb Weight) | 10% to 15% | 10% to 15% | 10% to 15% |
| Curb Weight (Approximate) | 2,670 lbs. | 3,060 lbs. | 3,280 lbs. |
| GVWR | 7,000 lbs. | 7,000 lbs. | 7,000 lbs. |
| Payload Capacity (Approximate) | 4,330 lbs. | 3,940 lbs. | 3,720 lbs. |
| Rear Ramp Door Opening - Width x Height | 94" x 72" | 94" x 72" | 94" x 72" |
| Side Door Opening - Width x Height | 32" x 72" | 32" x 72" | 32" x 72" |
| 12v Trailer End Connector | 7-Way | 7-Way | 7-Way |
| Tube Main Rails | 2" x 6" | 2" x 6" | 2" x 6" |

* Also available in tandem 5.2K axles model providing a 9,990 GVWR

STANDARD FEATURES

- Flat Roof/V-Nose Profile
- 15" Radial Tires with Silver Mod Wheels
- Smooth Aluminum Radius Fenderettes
- White .024 Aluminum Exterior (With Screws)
- 1-Piece Aluminum Roof
- · 12v LED Exterior Lighting
- 12v LED Slim Line Tail Lights
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist & 16" Ramp Extension
- 32" Side Door with Bar Lock
- 12v Dome Light with Self-Switch
- · Economy Sidewall Liner
- 3/4" High Performance PlexCore™ Decking
- 500 lb. Surface Wall Mounted Rope Rings (4)
- Spring Axles with 4" Drop
- E-Z Lube[®] Hubs
- Electric Brakes with Breakaway Kit
- Undercoated Chassis
- 16" OC Vertical Posts
- 24" OC Crossmembers
- 24" OC Tube Roof Bows
- 1-Year Limited Warranty

DELUXE PACKAGE UPGRADES

- .030 Aluminum Exterior
- Exterior Color Options
- 3/8" PlexCore™ Sidewall Liner
- 5,000 lb. Floor D-Rings (4)







