



**AMERICAN
HAULER**

HAULING THE AMERICAN SPIRIT

ENTRY-LEVEL TRAILERS THE ARROW



Trailers shown may feature optional equipment available at an additional charge.

A STRAIGHT SHOT TO A GREAT VALUE!

The American Hauler **ARROW** is your path to dependable and low-maintenance cargo hauling that won't break the bank. It's a perfect fit for recreational and light-duty applications. Although classified as an "entry level" trailer, the ARROW is loaded with quality features found on much more expensive trailers. No matter your hauling needs . . . count on the **ARROW** to deliver your valuables safe and secure to your final destination.

SPECIFICATIONS

	AR58SA	AR610SA	AR612SA	AR714TA2	AR716TA2
Body (L x W)	9'4" x 5'0"	11'4" x 6'0"	13'4" x 6'0"	15'4" x 7'0"	17'4" x 7'0"
Overall (L x W x H)	11'4" x 6'8" x 7'1"	14'0" x 7'8" x 8'1"	16'0" x 7'8" x 8'1"	18'0" x 8'6" x 8'2"	20'0" x 8'6" x 8'2"
Interior (L x W x H)	9'1" x 4'9" x 5'6"	11'1" x 5'9" x 6'6"	13'1" x 5'9" x 6'6"	15'1" x 6'9" x 6'6"	17'1" x 6'9" x 6'6"
Platform Height	17"	17"	17"	18"	18"
Side Door	N/A	32" Bar Lock	32" Bar Lock	32" Bar Lock	32" Bar Lock
Rear Door W x H	Single Swing 54" x 60"	Ramp 66" x 72"	Ramp 66" x 72"	Ramp 78" x 72"	Ramp 78" x 72"
Axle Quantity	Single	Single	Single	Tandem	Tandem
Brakes with Breakaway Kit	N/A	Optional	Optional	Electric	Electric
Radial Tire Size Tire Load Range	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C	ST205/75R15 C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"
Hitch Weight (% of curb weight)	10-15%	10-15%	10-15%	10-15%	10-15%
Curb Weight (Approx.)	965 lbs.	1,090 lbs.	1,225 lbs.	1,955 lbs.	2,115 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approx.)	2,025 lbs.	1,900 lbs.	1,765 lbs.	5,045 lbs.	4,885 lbs.
Tube Main Rails	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"
12v Connector	4-Way	4-Way	4-Way	7-Way	7-Way

STANDARD FEATURES

- Flat Roof with Sharp V-Nose Profile
- 16" OC Vertical Posts
- 24" OC Crossmembers
- 24" OC Tube Roof Bows
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit (Tandem Axle Models Only)
- Chassis Undercoated
- Ball Coupler Hitch
- Safety Chains to D.O.T Standards
- 15" Radial Tires with Silver Mod Wheels
- Smooth Aluminum Radius Fenders
- 1-Piece Seamless Aluminum Roof
- White .024 Aluminum Exterior with screws
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist (Single Swing Door on 5'W Models)
- 16" Ramp Extension
- 32" Side Door with Bar Lock (No Side Door on 5'W Models)
- 12v LED Exterior Lighting
- 12v LED Slim Line Tail Lights
- 12v LED Dome Light with Self-Switch
- 3/4" High Performance PlexCore™ Interior Floor
- Economy Sidewall Liner
- 500 lb. Surface Mounted Wall Rope Rings (4)*
- 1-Year Limited Warranty

• Ask about our popular **DELUXE Package** with .030 Exterior, ATP Nose Trim, 3/8" PlexCore™ Sidewalls, and 5000 lb. Floor D-Rings.



5' x 8' Arrow with optional rear ramp door



7' x 16' Arrow with Deluxe Package

