

---

# POWER WHEN YOU NEED IT MOST

---

## ONAN P9500DF

9,500-Watt Dual Fuel (Gas/LPG) Portable Generator

Gas: 7,500 Running Watts | 9,500 Peak Watts

Propane: 6,750 Running Watts | 8,550 Peak Watts



### **PUSH BUTTON & REMOTE START**

Pull cord backup



### **DUAL FUEL WITH JUST THE FLIP OF A SWITCH**



Easily switch from gas to propane with a fuel capacity of 6.6 gallons



### **ESSENTIAL DATA DISPLAY**

VFT Data Center displays volts, frequency, run time, maintenance reminders and lifetime hours

### **FEATURES**

- Dependable 420cc OHV 4-Stroke Cummins Onan engine
- Fuel gauge on top of 6.6-gallon gasoline tank
- Battery charging port with charger included
- 3-Year Warranty



**ONAN P9500DF SPEC SHEET**

SPECIFICATIONS	
Part Number	A058U967
Gasoline Running Watts	7,500
Gasoline Peak Watts	9,500
Gasoline Running Amps	62.5 A @ 120 V 31 A @ 240 V
Gasoline Peak Amps	79 A @ 120 V 39 A @ 240 V
Propane Running Watts	6,750
Propane Peak Watts	8,550
Propane Running Amps	56 A @ 120 V 28 A @ 240 V
Propane Peak Amps	71.25 A @ 120 V 35.6 A @ 240 V
AC Voltage	120/240 Volts
AC Frequency	60 Hz
Total Harmonic Distortion (THD)	≤23%
Automatic Voltage Regulator (AVR)	Yes
Starting System	Electric, Remote, Recoil
Battery	Included
Battery Charger Included	Yes
Remote Start Fob Included	Yes (factory paired)
Remote Start Distance (yards/meters)	109 yd (100 m)
Push Button Start	Yes
Engine Displacement	420 cc
Engine Brand	Cummins Onan
Engine Type	OHV 4 Stroke
Engine Speed	Constant
Operational Volume (dBA)	As low as 74 dBA
Carburetor Kit Required to Operate at Altitude	Yes, above 2,000 ft
Auto Idle Control	No
Built-in Inverter	No
Engine Lubrication	Splash
Recommended Oil	SAE 10W30
Oil Bottle Size (included)	1.1 qt / 1.1 L
Oil Capacity (Quarts/Ounces)	1.1 qt / 1.1 L
Low Oil Shutdown	Automatic
Fuel Type	Propane or Unleaded Gasoline, 10% Ethanol or less
Fuel Shut Off	Manual
Fuel Tank Capacity (Gallons/Liters)	6.6 gal (25 L)
Gas - Run Time at %25 Load (hrs)	16 hrs
Gas - Run Time at %50 Load (hrs)	11 hrs

Propane - Run Time at 25% Load (hrs) With 20-lb Standard Propane Tank	8 hrs
Gasoline Fuel Gauge	Yes
Choke Type	Automatic
Choke Location	Above Air Filter
AC Outlets	(1) 120/240 V 30 A (L14-30R) (2) Duplex 120 V 20 A GFCI (5-20R)
DC Outlets	(2) 5V USB
Ground	Neutral Bonded
Covered Outlets	Yes
Manual Transfer Switch Ready	Yes
GFCI Outlets	Yes
VFT Data Center (volts, frequency, run time, maintenance reminders, lifetime hours)	Yes
RV-Ready Outlet	No
Overload Protection (circuit breaker)	Yes
Handle Style	Single Handle with Foam Grip
Wheel Kit Included	Yes
Wheel Size	10 in Diameter, 2.5 in Wide
Frame Thickness in (mm)	1.25 in (25 mm)
Emissions	EPA, CARB
Canada CSA Compliant	Yes
Spark Arrestor	Yes
Residential Warranty	3 Years
Commercial Warranty	1 Year
Assembled Length in (mm)	27.25 in (692 mm)
Assembled Width in (mm)	26.25 in (667 mm)
Assembled Height in (mm)	26.25 in (667 mm)
Extended Length in (mm)	40.7 in (1,033.9 mm)
Carton Length in (mm)	31 in (787 mm)
Carton Width in (mm)	21.75 in (552 mm)
Carton Height in (mm)	23.25 in (591 mm)
Dry Unit Weight lb (kg)	194 lb (88 kg)
Shipping Weight lb (kg)	202 lb (91.6 kg)



**Cummins Inc.**  
**Box 3005**  
**Columbus, IN 47202-3005**  
**U.S.A.**

cummins.com

Bulletin 5300165 Produced in U.S.A. Rev. 3/22  
 ©2022 Cummins Inc.