



83" Wide Ultra Duty Dump Trailers



Standard Features & Specifications

GVWR:	10K: 4,490 kg (9,900 lbs.) 14K: 6,350 kg (14,000 lbs.)
Axle(s) & Suspension:	10K: (2) 6,000 lbs. Axles 14K: (2) 7,000 lbs. Axles w/ Easy Lube Spindles, Slipper Spring Suspension
Tires:	10K: ST225/75R15 LRD Radial 14K: ST235/80R16 LRE Radial
Brakes:	Electric on Both Axles
Coupler:	Adjustable 2-5/16" Coupler or 3" Lunette Eye
Jack:	12,000 lbs. Drop Leg Jack
Hoist Features:	<ul style="list-style-type: none"> • 3,000 psi Hydraulic Power Pack, 20' Hand Remote and Wireless Remote • 10' - 14' Models: 5" Hydraulic Cylinder & Scissor Hoist • 16' Models: 6" Hydraulic Cylinder & Scissor Hoist • Interstate Extreme Cycle Battery and Plug in Charger • Lockable Steel Toolbox
Sides:	20" Steel + 11" Wood Plank
Door:	<ul style="list-style-type: none"> • Barn Doors with Cam Lock • Two-way Gate
Load Cover:	Shielded Tarp & Roller
Deck Height:	29"
Floor:	Steel
Tongue Length:	52"
Tie Downs:	(4) Heavy Duty Welded In D-rings
Spare Tire Mount:	Passenger's Side of Box
Lights:	Transport Canada & D.O.T. Approved, Sealed Beam, L.E.D.
Electrical/Plug:	Sealed Harness & 7-way RV Plug

Finish:	Powder Coat + Scorpion Stone Guard
Finish Prep:	Sandblasted & Phosphate Etched

Popular Options

Spare Tire	55" High Sides
Tarp cover	Heavy Gauge Floor
Hydraulic Brakes	Additional D-rings
48" High Sides	Aluminum Wheels
Tri-axle 21KTR	Gooseneck
Deckover Option 94" Wide	Galvanize Trailer
HD Fenders	6' Ramps

Models

DT8312-10K	83" x 142.5"	1,528 kg (3,368 lbs.)
DT8314-10K	83" x 166.5"	1,622 kg (3,575 lbs.)
DT8312-14K	83" x 142.5"	1,640 kg (3,615 lbs.)
DT8314-14K	83" x 166.5"	1,775 kg (3,913 lbs.)
DT8316-14K	83" x 190.5"	2,223 kg (4,901 lbs.)

Dealer Information & Pricing

