





	CLASSIC				ESTATE			GRAND		
	353FLFB	<b>40FDEN</b>	4002Q	42QBQ	393FLT	394FKDS	395RET	42DL	42FK	42FLDL
HITCH WEIGHT:	1290 lb.	1295 lb.	1260 lb.	1325 lb.	1535 lb.	1555 lb.	1468 lb.	1855 lb.	1780 lb.	1720 lb.
UVW:	8679 lb.	9779 lb.	10299 lb.	11759 lb.	11029 lb.	10134 lb.	11357 lb.	12719 lb.	12469 lb.	12209 lb
CCC:	2811 lb.	1716 lb.	1161 lb.	1566 lb.	2506 lb.	1621 lb.	2111 lb.	1136 lb.	1311 lb.	1511 lb.
EXTERIOR LENGTH:	38' 3"	42' 6"	43' 7"	42'10"	40′ 5″	40' 8"	40'10"	41′ 8″	43'	41'7"
EXTERIOR HEIGHT:	11′ 11″	11' 11"	12' 3"	12' 3"	12' 8"	12' 8"	12' 8"	13′ 4″	13' 4"	13' 4"
EXTERIOR WIDTH:	96″	96″	96″	96″	102"	102"	102″	102″	102"	102″
FRESH WATER:	39 gal.	40 gal.	39 gal.	40 gal.	39 gal.	39 gal.	39 gal.	40 gal.	40 gal.	40 gal.
GRAY WATER:	50 gal.	40 gal.	90 gal.	80 gal.	80 gal.	90 gal.	80 gal.	80 gal.	80 gal.	80 gal.
BLACK WATER:	40 gal.	40 gal.	80 gal.	80 gal.	40 gal.					
AWNING SIZE:	21'	21'	21'	20'	20'	21'	20'	20'	19'	20'

# SALEM PRODUCT FAMILY



**FREE** MEMBERSHIP to Forest River Owners' Group

Scan this barcode using

a OR Reader on your

smart phone to learn

more about Forest River.

Learn More

www.forestriverfrog.com

A Berkshire Hathaway company

FSX

CRUISE LITE

SALEM

CLASSIC / ESTATE / GRAND VILLA

HEMISPHERE



### 24/7 EMERGENCY ROADSIDE ASSISTANCE WITH VEHICLE PURCHASE

TOWING JUMP-STARTS TIRE CHANGES FLUID DELIVERY LOCKOUT SERVICE

WINCH-OUT MOBILE MECHANIC TECHNICAL SUPPORT DEALER LOCATOR SERVICES



\*VALID FOR 1 YEAR FROM DATE OF PURCHASE

# **CUSTOMER SATISFACTION**



www.ForestRiverBuyLocal.com



**PRE-DELIVERY INSPECTION FACILITY** 20,000 square feet of quality assurance. The bare essentials for a premium product. This state-of-the-art facility gives immediate daily feedback to production for quality assurance in every unit built.

## **Specification Definitions**

**GVWR (Gross Vehicle Weight Rating)** - is the maximum permissible weight of the unit when fully loaded. It includes all weights, inclusive of all fluids, cargo, optional equipment and accessories. For safety and product performance do NOT exceed the GWWR.

GAWR (Gross Axle Weight Rating) - is the maximum permissible weight, including rargo, fluids, optional equipment and accessories that can be safely supported by a combination of all axles.

UVW (Unloaded Vehicle Weight)\* - is the typical weight of the unit as manufactured at the factory. It includes all weight at the unit's axle(s) and tongue or pin and LP Gas. The UVW does not include cargo, fresh potable water, additional optional equipment or dealer installed accessories.

\*Estimated average based on standard build optional equipment.

All information contained in this brochure is believed to be accurate at the time of publication. However, during the model year, it may be necessary to make revisions and Forest River, Inc., reserves the right to make all such changes without notice, including prices, colors, materials, equipment and specifications as well as the addition of new models and the discontinuance of models shown in this brochure. Therefore, please consult with your Forest River dealer and confirm the existence of any materials, design or specifications that are material to your ourchase decision. Litho. U.S.A. FOR 1609 P/W: 2019.01.22

### MEET YOUR VILLA DEALER

CCC (Cargo Carrying Capacity)\*\* - is the amount of weight available for fresh potable water, cargo, additional optional equipment and accessories. CCC is equal to GWWR minus UVW. Available CCC should accommodate fresh potable water (8.3 lbs per gallon). Before filling the fresh water tank, empty the black and gray tanks to provide for more cargo capacity.

\*\* Estimated average based on standard build optional equipment

Each Forest River RV is weighed at the manufacturing facility prior to shipping. A label identifying the unloaded vehicle weight of the actual unit and the cargo carrying capacity is applied to every Forest River RV prior to leaving our facilities.

The load capacity of your unit is designated by weight, not by volume, so you cannot necessarily use all available space when loading your unit.