





Own the Outdoors

**CONVENTIONAL TRAVEL TRAILERS** 





MR182RB



MR19BH



# FEATURES STANDARDS

- » Magnum Roof System
- » Fiberglass Insulation
- » Pocket Screwed Lumbercore Cabinet Construction
- » Linoleum Throughout
- » 5/8" Main Floor Decking
- » PVC Roofing Membrane (15 Year Warranty/Non-Prorated)
- » Gas DSI Water Heater
- » Black Front Diamond Plating
- » 120V G.F.C.I Protected Exterior Receptacle
- » Bumper with Drain Hose Carrier & End Caps
- » Omni-Directional Digital TV/AM/FM Antenna with Powered Amplifier
- » Electric Brakes
- » Nitrogen Filled Tires
- » Solar Prep
- » Tinted Safety-Glass Windows
- » Wide Entrance Doors with Screen Door & Window
- » Galvanized Steel Wheel Wells
- » (2) 30lb. LP Bottles with Bottle Cover (Dual Axle Models)
- » 20lb. LP Bottle (Single Axle Models)

- » Power Awning with LED Lighting & Integrated Speakers
- » Stabilizer Jacks
- » Power Tongue Jack (Dual Axle Models)
- » Spare Tire with Carrier
- » Docking Station with Tank Flush (Dual Axle Models)
- » EZ-Store Detachable Power Cord
- » 12V CD/DVD Stereo with USB Input
- » Double-Over-Double Bunk Bed with 600lb. Capacity
- » 12V Powered Bathroom Vent
- » Shower Surround
- » Stainless Steel Appliances
- » 3 Burner Cooktop with 17" Oven & Microwave (Dual Axle Models)
- » Heated Enclosed Underbelly (Dual Axle Models)
- » Magnet Catches for Baggage Doors
- » Rubber LP Lines
- » Pet Friendly
- » No Heat Registers in Floor
- » Pet Tie Out with Bottle Opener (Dual Axle Models)
- » MyPillow® Pet Bed (Dual Axle Models)

	MR171RD**	MR180BHS**	MR182RB**	MR19BH**	<b>MR20FBS</b>	MR20MB	MR21FB	MR21RBS	<b>MR23RLS</b>	MR26BH	<b>MR26BHS</b>	MR27BHS	MR27RLI	MR282BH	MR32BHS
Square Feet	145	159	153	147	165	166	174	221	220	203	249	263	300	269	319
Unloaded Vehicle Weight (lbs.)	3,445	3,735	3,515	3,515	4,280	4,185	4,275	5,660	5,420	4,735	5,725	6,255	7,195	6,410	7,600
Dry Hitch Weight (Ibs.)	395	375	345	370	400	490	545	575	690	585	720	775	1,035	610	835
Gross Vehicle Weight Rating (GVWR)	4,500	4,900	4,250	4,450	6,000	5,250	6,000	7,200	6,500	6,500	7,500	8,500	8,995	8,500	9,250
Cargo (Gross)	1,055	1,165	735	935	1,720	1,065	1,725	1,540	1,080	1,765	1,775	2,245	1,800	2,090	1,650
Exterior Length (Pin to Rear)	21' 8"	22' 0"	22' 9"	22' 2"	23' 6"	24' 4"	25' 7"	27' 3"	29' 1"	29' 4"	30' 7"	31' 9"	33' 10"	32' 5"	36' 5"
Exterior Height	10' 2"	10' 3"	10' 2"	10' 5"	10' 6"	10' 5"	10' 6"	10' 9"	11' 0"	10' 6"	11' 1"	11' 4"	11' 2"	11' 3"	11' 0"
Exterior Width	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"	8' 0"
Exterior Width (Slides Out)	N/A	10' 0"	N/A	N/A	9' 5"	N/A	N/A	10' 11"	10' 11"	N/A	11' 0"	11' 0"	13' 0"	11' 0"	10' 11"
Interior Height	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"	6' 9"
Fresh Water Capacity (Gal.)*	26	26	26	26	48	48	48	48	48	48	48	48	48	48	48
Gray Waste Water Capacity (Gal.)	19.9	19.9	19.9	32.5	32.5	32.5	32.5	65	32.5	32.5	32.5	32.5	40	65	32.5
Black Waste Water Capacity (Gal.)	19.9	19.9	19.9	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5	32.5
LP Capacity (lbs.)	20	20	20	20	60	60	60	60	60	60	60	60	60	60	60
Tire Size	14"	15"	14"	15"	14"	14"	14"	14"	14"	14"	15"	15"	15"	15"	15"
Awning Size	9'	11'	11'	13'	12'	15'	16'	19'	19'	19'	16'	18'	20'	20'	20'

\*Includes Water Heater

\*\*Single Axle Models

- **OPTIONS**
- » 15K BTU Air Conditioner (Dual Axle Models)
- » 50 amp service with 2nd 13.5K A/C (Select Dual Axle Models)

#### SLIDE OUTS

- » Exterior slide out walls built with studs 16" on center
- » Residential fiberglass insulation full wall
- » Laminated metal endwalls with residential fiberglass insulation

#### **4** FLOORS

- » Wood reinforced framed construction 16" on center perpendicular to frame crossmembers
- » Built-in galvanized wheel wells
- » Insulated with residential fiberglass insulation, anti-puncture moisture barrier woven underbelly material wrapped around floor

### 2 DOORS & LOCKS

- » Dark tinted safety glass
- » Full-width entrance door with screen and window
- » Baggage and storage doors with magnetic latches

#### **5** SIDEWALLS

- » Exterior walls with studs 16" on center for consistency and strength
- » Residential fiberglass insulation secured in between each stud for maximum efficiency
- » Superior metal-thicker than average metal with S-locking design for maximum rigidity

#### <sup>3</sup> ROOF

- » Strength tested Magnum Roof System-50% stronger than the competition with 4,500lb. rating
- » 3/8" residential decking with residential fiberglass insulation
- » Sealed with seamless one-piece material that is 30% lighter, reflects heat and has an embossed finish.

## 6 MAIN BODY

7 HEATING SYSTEM

- » Aluminum wheels with nitrogen filled tires
- » Structural steel I-beam with stamped cross members for added strength
- » Wide-stance axles for stability with various size axles based on model
- » Flexible LP gas lines for longevity and durability

 » High efficiency furnace provides heat down to the fully enclosed underbelly\*
» Holding tanks are warmed by the forced air heat which helps prevent freeze-ups





\* Heated enclosed underbelly is on dual axle models only

> Highland RIDGE RV Own the Outdoors

# For more information visit us at: www.HighlandRidgeRV.com

Due to continual research and advances, manufacturer reserves the right to change specifications, design, price, and equipment without notice, and assumes no responsibility for any error in the literature. Some items shown are not included as standard or optional equipment.

©2019 Highland Ridge RV, Shipshewana, Indiana – Published Date March 13, 2020 11:31 AM

We stand behind our products. At Highland Ridge RV, we are one of the few manufacturers that have a 3-Year Limited Structural Warranty.