# 2022 BACKCOUNTRY MODELS



# **BACKCOUNTRY**

Loaded with crossover-specific features for spending equal time riding on- or off-trail.



## // PACKAGE HIGHLIGHTS

- High-quality HPG shock package
- 4.5 in. digital display

PULTA A & ENGINE

- RAS™ 3 front suspension
- cMotion™ rear suspension
- · Electric starter
- Rotax® 850 E-TEC® and 600R E-TEC engines available Improved deep-snow running boards with large

ANNE E-TEC®

- Glove box with 4 L/1 gal of storage
- · Low windshield with deflectors
- pDrive™ clutch with clickers
- Transparent handguards

- Open toe-hold
- NEW standard with two sets of LinQ attachment points
- DS 2 skis
- · Adjustable ski stance
- Belt monitoring system (850 E-TEC only)

RUIAX" ENGINE	850 E-1EL®	Liquid-cooled, two-stroke, eRAVE™	
Engine details	Liquid-cooled, two-stroke, eRAVE™		
Horsepower	165	125	
Cylinders - Displacement	2 - 849 cc	2 - 599.4 cc	
Bore - Stroke	82 mm - 80.4 mm	72.3 mm - 73 mm	
Carburation	E-TEC® direct injection with additional booster injectors	E-TEC® direct injection	
Fuel type – Octane	Premium unleaded – 91	Premium unleaded – 91	
Fuel tank	36 L/9.5 US gal	36 L/9.5 US gal	
Oil tank capacity	3.4 L/3.6 qt	3.4 L/3.6 qt	
POWERTRAIN			
Drive clutch	pDrive™ with clickers	pDrive™ with clickers	
Driven clutch	QRS Vent Plus	QRS Vent	
Drive sprocket pitch	73 mm/2.86 in.	73 mm/2.86 in.	
DRY WEIGHT			
Dry weight	219 kg/483 lb	212 kg/466 lb	
DIMENSIONS			
Overall vehicle length	3,174 mm/125 in.		
Overall vehicle width	1,140 to 1,180 mm/44.9 to 46.5 in.		
Overall vehicle height	1,283 mm/50.5 in.		
Ski stance	975 or 1,020 mm/38.4 or 40.2 in.		
Track	Cobra:		
(Length x Width x Profile)	146 x 15 x 1.6 in.		

850 F-TFC®

Catalyst Grey / Octane Blue	
Black Black	
SUSPENSION	
Front suspension	RAS™ 3
Front shock	HPG™ Plus
Front suspension travel	220 mm/8.7 in.
Rear suspension	cMotion™
Center shock	HPG™
Rear shock	HPG™
Rear suspension travel	239 mm/9.4 in.
FEATURES	
Frame	REV® Gen4
Bodywork	Narrow design
Skis	Pilot™ DS 2
Seating	Trail performance
Handlebar	U-shaped aluminum with J-hooks/ Transparent handguards
Riser block height	120 mm/4.7 in.
Starter	Electric
Reverse	RER™
Brake system	Brembo brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	4.5 in. digital display
Windshield	360 mm/14 in.
Runner – Carbide	Square 3/8 – 4 in.
Bumpers (front/rear)	Std/Std

## 2022 BACKCOUNTRY™

## // FEATURE HIGHLIGHTS



## 1 Rotax® 850 E-TEC® and 600R E-TEC® engines

Incredible power and unmatched dynamic response with exclusive E-TEC® direct-injection technology. Plasma-coated, mono-block cylinders are used for exceptional durability, while the precision of E-TEC® injection means you get excellent fuel and oil economy.



## 2 High-quality HPG shock package

Extremely capable high-pressure gas shocks by KYR



## 3 cMotion™ rear suspension

Crossover-specific suspension uses best principles of the rMotion  $^{\text{TM}}$  trail and tMotion  $^{\text{TM}}$  mountain skids for confident cornering and agile boondocking.



BACKCOUNTRY™ 146 850 E-TEC® SHOWN



## 4 Deep-snow running boards

Massive, strategically shaped openings keep the boards clear. A tall extruded edge adds stiffness and has aggressive boot grips.



## <sup>5</sup> Pilot™ DS2 skis

Single keel with excellent sidehilling bite, thanks to thin outer edges. Narrow and thin, yet stiff. Shorter behind the spindle with flat tail for easier counter-steering and sidehilling.



## 6 pDrive™ clutch with clickers

Clicker ramps allow easy adjustment for top RPM. Ultra-responsive shifting, impressive RMP consistency, lightweight and maintenance-free.





# **BACKCOUNTRY** X°

A 50-50 sled with the most advanced technology, plus off-trail capability and rough-trail performance.



## // PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC® engine
- High-performance shock package
- 7.8 in. wide LCD display with BRP Connect available
- RAS™ 3 front suspension
- cMotion<sup>™</sup> rear suspension

**ROTAX® ENGINE** 

• E-TEC $^{\odot}$  SHOT $^{\text{TM}}$  starter available

- Improved deep-snow running boards with large openings
- Glove box with 4 L/1 gal of storage
- · Low windshield
- Backlit multifunction handlebar controls
- pDrive™ clutch with clickers
- Transparent handquards

850 E-TEC®

PowderMax†: 146 x 16 x 2.0 in. opt.

- Open toe-hold
- NEW standard with two sets of LinQ attachment points
- DS 2 skis
- · Adjustable ski stance
- Belt monitoring system

Liquid-cooled, two-stroke, eRAVE™
165
2 - 849 cc
82 mm - 80.4 mm
E-TEC® direct injection with additional booster injectors
Premium unleaded – 91
36 L/9.5 US gal
3.4 L/3.6 qt
pDrive™ with clickers
QRS Vent Plus
73 mm/2.86 in.
<del></del>
209 kg/462 lb
7.17/ /105:
3,174 mm/125 in.
1,140 to 1,180 mm/44.9 to 46.5 in.
1,283 mm/50.5 in.
975 or 1,020 mm/38.4 or 40.2 in.
Cobra: 146 x 15 x 1.6 in.
Ice Cobra: 146 x 15 x 1.6 in. opt.

Scandinavian Blue / Orange Crush

Black

SUSFERSION	
Front suspension	RAS™ 3
Front shock	HPG™ Plus
Front suspension travel	220 mm/8.7 in.
Rear suspension	cMotion™
Center shock	HPG™ Plus
Rear shock	KYB⁺ PRO 36 Easy-Adjust
Rear suspension travel	239 mm/9.4 in.

#### CEATHDEC

Frame	REV® Gen4
Bodywork	Narrow design
Skis	Pilot™ DS 2
Seating	Trail performance
Handlebar	U-shaped aluminum with J-hooks/ Transparent handguards
Riser block height	120 mm/4.7 in.
Starter	Electric, SHOT (opt. select configurations)
Reverse	RER™
Brake system	Brembo racing brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	7.2 in. wide digital display 7.8 in. wide LCD color display (opt.)
Windshield	360 mm/14 in.
Runner – Carbide	Square 3/8 in. – 4 in.
Bumpers (front/rear)	Std/Std

## 2022 BACKCOUNTRY™ X®

## // FEATURE HIGHLIGHTS



## 1 Rotax® 850 E-TEC® engine

Next generation of the most advanced directinjection 2-stroke engine technology. Designed for reliability and durability with proven 4-stroke and long-lasting automotive technologies.



## 2 Premium shock package

HPG Plus front and center shocks. KYB PRO 36 EA rear shock featuring compression adjustment with easy-adjust knob. All four shocks are aluminum and rebuildable/revalvable.



## 3 cMotion™ rear suspension

Crossover-specific suspension uses best principles of the rMotion trail and tMotion mountain skids for confident cornering and agile boondocking.



BACKCOUNTRY™ X® 146 850 E-TEC® SHOWN



## 4 Large panoramic 7.8 in. wide LCD color display available

Wide-screen full-color display lets riders truly customize their ride from behind the bars. Choose your preferred sled info, and see app integrated-information in a split-screen format with GPS, Bluetooth music, helmet-to-helmet communication and more.



## <sup>5</sup> Pilot™ DS2 skis

Single keel with excellent sidehilling bite, thanks to thin outer edges. Narrow and thin, yet stiff. Shorter behind the spindle with flat tail for easier counter-steering and sidehilling.



#### 6 E-TEC® SHOT™ starter

Push-button starting with almost no added weight. Uses energy stored in the lightweight ultracapacitor to turn the magneto and with E-TEC® technology, starts the engine.





# BACKCOUNTRY" X-RS°

The most aggressive crossover vehicle with snocross attitude and go-anywhere capability.



## // WHAT'S NEW

- Two *ULTIMATE* color options with panel wrap: supreme look and finish, maximum protection
- Standard with two sets of LinQ attachment points

## // PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC® engine
- High-performance KYB PRO shock package
- 7.8 in. wide LCD display with BRP Connect available
- RAS<sup>™</sup> 3 front suspension
- cMotion™ rear suspension

- E-TEC® SHOT™ starter available
- RS running boards
- Glove box with 4 L/1 gal of storage
- Backlit multifunction handlebar controls
- pDrive™ clutch with clickers

- Transparent handguards
- Open toe-hold
- DS 2 skis
- Adjustable ski stance
- Belt monitoring system

ROTAX® ENGINE	850 E-TEC®	
Engine details	Liquid-cooled, two-stroke, eRAVE™	
Horsepower	165	
Cylinders - Displacement	2 - 849 cc	
Bore - Stroke	82 mm – 80.4 mm	
Carburation	E-TEC® direct injection with additional booster injectors	
Fuel type – Octane	Premium unleaded - 91	
Fuel tank	36 L/9.5 US gal	
Oil tank capacity	3.4 L/3.6 qt	
POWERTRAIN		
Drive clutch	pDrive™ with clickers	
Driven clutch	QRS Vent Plus	
Drive sprocket pitch	73 mm/2.86 in.	
DRY WEIGHT		

Dry weight	214 kg/472 lb (146 in.)
	220 kg/485 lb (154 in.)
DIMENSIONS	
Overall vehicle length	3,174 mm/125 in. (146 in.)
	3,284 mm/129.3 in. (154 in.)
Overall vehicle width	1,140 to 1,180 mm/44.9 to 46.5 in.
Overall vehicle height	1,283 mm/50.5 in.
Ski stance	975 or 1,020 mm/38.4 or 40.2 in.
Track	Cobra: 146 x 15 x 1.6 in.
(Length x Width x Profile)	Ice Cobra: 146 x 15 x 1.6 in. opt.
	PowderMax†: 146 x 16 x 2.0 in. opt.
	154 x 16 x 2.0 in.
	154 x 16 x 2.5 in. opt.

#### CULUK

ULTIMATE Liquid Titanium / Carbon Black

ULTIMATE Black

## SUSPENSION

Front suspension	RAS™ 3
Front shock	KYB† PRO 36 R Easy-Adjust
Front suspension travel	220 mm/8.7 in.
Rear suspension	cMotion™
Center shock	KYB† PRO 40 Easy-Adjust
Rear shock	KYB† PRO 40 Easy-Adjust
Rear suspension travel	239 mm/9.4 in. (154, 165 in.)

#### **FEATURES**

LAIUKLO	
Frame	REV® Gen4
Bodywork	Narrow design
Skis	Pilot™ DS 2
Seating	Trail performance
Handlebar	U-shaped aluminum with J-hooks/ Transparent handguards
Riser block height	120 mm/4.7 in.
Starter	Electric, SH0T (opt. select configurations)
Reverse	RER™
Brake system	Brembo racing brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	7.2 in. wide digital display 7.8 in. wide LCD color display (opt.)
Windshield	Optional
Runner - Carbide	Round 7/16 - 4 in.
Bumpers (front/rear)	Std/Std

## 2022 BACKCOUNTRY™ X-RS°

## // FEATURE HIGHLIGHTS



## 1 Rotax® 850 E-TEC® engine

Next generation of the most advanced directinjection 2-stroke engine technology. Designed for reliability and durability with proven 4-stroke and long-lasting automotive technologies.



## 2 High-performance KYB PRO shock package

Extreme-capability, extreme-durability shocks for control in the toughest conditions. Easy adjust-equipped for dialed-in compression and rebound.



## 3 cMotion™ 146 or 154 rear suspension

Crossover-specific suspension uses best principles of the rMotion  $^{\text{TM}}$  trail and tMotion  $^{\text{TM}}$  mountain skids for confident cornering and agile boondocking.



BACKCOUNTRY™ X-RS® 146 850 E-TEC® SHOWN



## 4 Large panoramic 7.8 in. wide LCD color display available

Wide-screen full-color display lets riders truly customize their ride from behind the bars. Choose your preferred sled info, and see app integrated-information in a split-screen format with GPS, Bluetooth music, helmet-to-helmet communication and more.



## 5 RS running boards

Designed for aggressive stand-up riding, they are flatter for most of their length, wider and strong. Thicker aluminum sheet, plus front and rear reinforcements to withstand tough landings.



#### 6 E-TEC® SHOT™ starter

Push-button starting with almost no added weight. Uses energy stored in the lightweight ultracapacitor to turn the magneto and with E-TEC® technology, starts the engine.





# **BACKCOUNTRY**™ **SPORT**

For the value-oriented 50-50 rider wanting an advanced platform and modern engine technology.



## // PACKAGE HIGHLIGHTS

- Rotax® 600 EFI engine
- RAS<sup>™</sup> 3 front suspension
- cMotion™ rear suspension
- Electric starter

- Improved deep-snow running boards with large openings
- Glove box with 4 L/1 gal of storage
- Low windshield
- pDrive™ clutch

- Brembo brake with braided stainless-steel brake line
- NEW standard with two sets of LinQ attachment points
- DS 2 skis
- · Adjustable ski stance

ROTAX® ENGINE	600 EFI
Engine details	Liquid-cooled, two-stroke
Horsepower	85
Cylinders – Displacement	2 - 599.4 cc
Bore - Stroke	72.3 mm – 73 mm
Carburation	EFI
Fuel type – Octane	Regular unleaded – 87
Fuel tank	36 L/9.5 US gal
Oil tank capacity	3.4 L/3.6 qt
POWERTRAIN	
Drive clutch	pDrive™
Driven clutch	QRS
Drive sprocket pitch	73 mm/2.86 in.
DRY WEIGHT	
Dry weight	202 kg/446 lb
DIMENSIONS	
Overall vehicle length	3,174 mm/125 in.
Overall vehicle width	1,140 to 1,180 mm/44.9 to 46.5 in.
Overall vehicle height	1,283 mm/50.5 in.
Ski stance	975 or 1,020 mm/38.4 or 40.2 in.
Track	Cobra:
(Length x Width x Profile)	146 x 15 x 1.35 in.
	PowderMax <sup>†</sup> :
	146 x 16 x 2.0 in. opt.

COLOR	
Catalyst Grey / Black	
SUSPENSION	
Front suspension	RAS™ 3
Front shock	Motion Control
Front suspension travel	220 mm/8.7 in.
Rear suspension	cMotion™
Center shock	Motion Control
Rear shock	HPG™
Rear suspension travel	239 mm/9.4 in.
FEATURES Frame	REV® Gen4
Bodywork	Narrow design
Skis	Pilot™ DS 2
Seating	Trail compact
Handlebar	U-shaped aluminum with J-hooks
Riser block height	120 mm/4.7 in.
Starter	Electric
Reverse	RER™
Brake system	Brembo brake with stainless-steel braided brake line
Heated throttle lever/grips	Standard
Gauge type	Compact digital gauge
Windshield	360 mm/14 in.
Runner – Carbide	Square 3/8 in. – 4 in.

## 2022 BACKCOUNTRY™ SPORT

## // FEATURE HIGHLIGHTS



## 1 Rotax® 600 EFI engine

600 cc-class fuel-injected engine delivering 85 horsepower and outstanding economy at an incredible value. Design based on the 600R E-TEC with proven reliability and ease of ownership at its core with an outsized fun factor.



Saves time and energy, adding immense value for the rider.



## 3 cMotion™ rear suspension

Crossover-specific suspension uses best principles of the rMotion trail and tMotion mountain skids for confident cornering and agile boondocking.



BACKCOUNTRY™ SPORT 146 600 EFI SHOWN



## 4 RAS™ 3 front suspension

Similar geometry and steering to the RAS 3 mountain front end for capability and light steering feel on- and off-trail. Optimized for crossover usage, two ski stance positions dial in handling: 40.2 in. [102 cm] or 38.4 in. [97.5 cm].



## <sup>5</sup> Pilot™ DS2 skis

Single keel with excellent sidehilling bite, thanks to thin outer edges. Narrow and thin, yet stiff. Shorter behind the spindle with flat tail for easier counter-steering and sidehilling.



## 6 Ergo-step side panels

Design offers natural progression to three natural positions for different cornering styles, including a new, extreme-forward position.



