CHAPARRAL AZDEL

CHAPARRAL

ALL NEW 3RD A/C OPTION (SELECT MODELS)

Z STANDARD WITH WEATHER SHIELD U PLUS

е.,

WHEELS

IF

IJ

RRAL

APA

I U

COACHM



SCAN HERE FOR ADDITIONAL PHOTOS, 360 VIRTUAL TOURS, VIDEOS, & A COMPLETE LIST OF STANDARDS, OPTIONS & MORE


CHAPARRAL

YOUR LOCAL DEALER WWW.COACHMENRV.COM/FIFTHWHEELS



CHAPARRAL X-EDITION





LITE

Model	25RE	274BH	284RL	30RLS	30BHS
Carrying Capacity (lbs)	2,527	2,308	2,592	2,019	1,965
UVW (lbs)	7,273	8,692	8,908	8,981	9,535
GVWR (lbs)	9,800	11,000	11,500	11,000	11,500
Hitch Weight (lbs)	1,115	1,420	1,434	1,445	1,553
Exterior Height (Factoring STD. A/C Only)	12'	12'	12'	12'	12'
Fresh Water Capacity (gal)	40	40	40	40	40
Grey Water Capacity (gal)	33	66	66	66	66
Waste Water Capacity (gal)	33	33	33	33	33
Awning Length	13'	16'	11'	11'	15'
Wheel Size	16"	16"	16"	16"	16"
Exterior Length (Includes Bumper to Cap)	29' 10"	35' 11"	34' 2"	34' 2"	37
Interior Height (Coach)	81"	81"	81"	81"	81"
Axles Rating (lbs)	5,100	5,100	5,100	5,100	5,100
Tire Size	ST235/80R16E	ST235/80R16E	ST235/80R16E	ST235/80R16E	ST235/80R16E

	Model	355FBX	393MBX
	Carrying Capacity (lbs)	2,958	2,420
	UVW (lbs)	11,542	13,080
	GVWR (lbs)	14,500	15,500
	Hitch Weight (lbs)	2,008	2,498
	Exterior Height (Factoring STD. A/Cs Only)	13'	13'
	Fresh Water Capacity (gal)	48	48
	Grey Water Capacity (gal)	135	85
	Waste Water Capacity (gal)	90	45
	Awning Length	20'	20'
i.	Wheel Size	16"	16"
2	Exterior Length (Includes Bumper to Cap)	42' 6"	42' 6"
1	Interior Height (Coach)	85"	85"
C.W	Axles Rating (lbs)	7,000	7,000
	Tire Size	ST235/80R16G	ST235/80R16G
2	HEIGHT FACTORS 2ND 15P	K A/C (STA	NDARD)

X-EDITION





TOWING JUMP-STARTS TIRE CHANGES FLUID DELIVERY LOCKOUT SERVICE

5

MOBILE MECHANIC TECHNICAL SUPPORT DEALER LOCATOR SERVICES

FERIDERV

NOTO# CLUB **'VALID FOR 1 YEAR FROM DATE OF PURCHASE**

HEIGHT FACTORS MAIN A/C ONLY (2ND A/C OPTIONAL)

MID-PROFILE

Model	298RLS	334FL	336TSIK	360IBL	367BH	373MBRB	375BAF
Carrying Capacity (lbs)	2,425	2,600	2,980	2,550	3,172	1,969	2,078
UVW (lbs)	9,575	12,400	10,520	11,450	12,328	13,031	12,422
GVWR (lbs)	12,000	15,000	13,500	14,000	15,500	15,000	14,500
Hitch Weight (lbs)	1,935	2,708	1,880	2,100	2,194	2,219	2,152
Exterior Height (Factoring STD. A/Cs Only)	13'	13'	13′	13′	13′	13′	13'
Fresh Water Capacity (gal)	48	48	48	48	48	48	48
Grey Water Capacity (gal)	90	85	90	90	112	120	112
Waste Water Capacity (gal)	45	45	45	45	72	75	72
Awning Length	15'	20'	16'	18'	15'	17'	11'
Wheel Size	16"	16"	16"	16"	16"	16"	16"
Exterior Length (Includes Bumper to Cap)	34' 8"	42' 6"	37'	39' 9"	42' 6"	42' 6"	42' 6"
Interior Height (Coach)	85"	85"	85"	85"	85"	85"	85"
Axles Rating (lbs)	5,100	7,000	7,000	7,000	7,000	7,000	7,000
Tire Size	ST235/80R16E	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G	ST235/80R16G

COACHMEN OWNERS ASSOCIATION **FREE MEMBERSHIP**

www.coachmenowners.com

CUSTOMER SATISFACTION FOREST RIVER CCT IN CONTRACTION PREFERENTIAL encourages you to BUY

www.ForestRiverBuyLocal.com

LÕČÁL

Learn Nore





PRE-DELIVERY INSPECTION FACILITY

20,000 square feet of quality assurance. The bare essentials for a premium product. This state-of-the-art facility gives immediate daily feedback to production for quality assurance in every unit built.

oachmen Leader to the Great Outdoors

GVWR (GROSS VEHICLE WEIGHT RATING) - IS THE MAXIMUM PERMISSIBLE WEIGHT OF THE UNIT WHEN FULLY LOADED. IT INCLUDES ALL WEIGHTS, INCLUSIVE OF ALL FLUIDS, CARGO, OPTIONAL EQUIPMENT AND ACCESS FOR SAFETY AND PRODUCT PERFORMANCE DO NOT EXCEED THE GVWR.

GAWR (GROSS AXLE WEIGHT RATING) - IS THE MAXIMUM PERMISSIBLE WEIGHT, INCLUDING CARGO, FLUIDS JIPMENT, AND ACCESSORIES THAT CAN BE SAFELY SUPPORTED BY A COMBINATION OF ALL AXLES. UVW (UNLOADED VEHICLE WEIGHT)" - IS THE TYPICAL WEIGHT OF THE UNIT AS MANUFACTURED AT THE FACTORY. IT INCLUDES ALL WEIGHT AT THE UNIT'S AXLE(S) AND TONGUE OR PIN AND LP GAS. THE UVW DOES NOT INCLUDI CARGO, FRESH POTABLE WATER, ADDITIONAL OPTIONAL EQUIPMENT OR DEALER INSTALLED ACCESSORIES 'ESTIMATED AVERAGE BASED ON STANDARD BUILD OPTIONAL EQUIPMENT.

CCC (CARGO CARRYING CAPACITY)" - IS THE AMOUNT OF WEIGHT AVAILABLE FOR FRESH POTABLE WATER, CARGO, ADDITIONAL OPTIONAL EQUIPMENT AND ACCESSORIES. CCC IS EQUAL TO GVWR MINUS UVW. AVAILABLE CCC SHOULD ACCOMMODATE FRESH POTABLE WATER (8.3 LBS PER GALLON), BEFORE FILLING THE FRESH WATER TANK, EMPTY THE BLACK AND GRAY TANKS TO PROVIDE FOR MORE CARGO CAPACITY.

" ESTIMATED AVERAGE BASED ON STANDARD BUILD OPTIONAL EQUIPMENT. EACH FOREST RIVER RV IS WEIGHED AT THE MANUFACTURING FACILITY PRIOR TO SHIPPING. A LABEL IDENTIFYING THE UNLOADED VEHICLE WEIGHT OF THE ACTUAL UNIT AND THE CARGO CARRYING CAPACITY IS APPLIED TO EVERY FOREST RIVER RV PRIOR TO LEAVING OUR FACILITIES

THE LOAD CAPACITY OF YOUR UNIT IS DESIGNATED BY WEIGHT, NOT BY VOLUME, SO YOU CANNOT NECESSARILY USE ALL AVAILABLE SPACE WHEN LOADING YOUR UNIT.

ALL INFORMATION CONTAINED IN THIS BROCHURE IS BELIEVED TO BE ACCURATE AT THE TIME OF PUBLICATION. HOWEVER, DURING THE MODEL YEAR IT MAY BE NECESSARY TO MAKE REVISIONS. FOREST RIVER, INC., RESERVES THE RIGHT TO MAKE ALL SUCH CHANGES WITHOUT NOTICE, INCLUDING PRICES, COLORS, MATERIALS, EQUIPMENT, AND SPECIFICATIONS, AS WELL AS THE ADDITION OF NEW MODELS AND THE DISCONTINUANCE OF MODELS SHOWN IN THIS BROCHURE. THEREFORE. PLEASE CONSULT WITH YOUR FOREST RIVER DEALER AND CONFIRM THE EXISTENCE OF ANY MATERIALS. DESIGN. OR SPECIFICATIONS THAT ARE MATERIAL TO YOUR PURCHASE DECISION. OPTIONAL EQUIPMENT IS NOT FACTORED IN UNIT SPECS. = WHERE APPLICABLE. (REV. 1-1-23)

