



ROTAX® ENGINE	850 E-TEC Turbo R
Engine details	Liquid-cooled, two-stroke, turbocharged, 3-D R.A.V.E.™
Cylinders	2
Displacement	849 cc
Bore	82 mm
Stroke	80.4 mm
Maximum engine speed	7900 RPM
Carburation	Electronic Direct Injection with additional booster injectors
Recommended fuel type	Unleaded
Minimum octane	91
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

	Platinum Silver Satin /
OLOUR	Evo Red

DIMENSIONS

Vehicle overall length*	3190 mm (3900) 3335 mm (4100)
Vehicle overall width	1055 mm
Vehicle overall height	1280 mm
Ski stance	863 mm
Track nominal width	381 mm
Track nominal length	3912 mm 4178 mm
Track profile height	76 mm PowderMax X-Light

POWERTRAIN

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, adjustable brake lever, aluminium master cylinder

SUSPENSION

Front suspension	LFS
Front shock	KYB 36 Plus Kashima
Rear suspension	PPS ² -DS+
Center shock	KYB 36 Plus Kashima
Rear shock	KYB 36 Plus Kashima

DRY WEIGHT

Dry weight 3900: 216 kg 4100: 218 kg

FEATURES

Frame	Radien²
Skis	Blade DS+
Seating	Shredder DS, 1-up
Handlebar	U-type aluminium with hooks, low grab handle
Riser block height	120 mm
Starter	Manual with SHOT
Reverse	RER

Heated throttle lever	Standard
Heated grips	Standard
Gauge	4.5 in. digital display 10.25 in. Color Display
USB power outlet	Yes, in front compartment
LinQ attachment	2 pairs



^{*}Overall vehicle length without snow flap.