

## The DSTT Series: All Sport, All the Time.

- Radial Tires
- · LED Lights, Inside and Out
- One Piece Aluminum Roof
- 3/4" High-Performance Floor
- Rubberized Coating on Hitch and Rear Bumper

Scan to learn more!





## 1500 Standards

Spring Axle with 4" Drop
Radial Tires on Gray Wheels
Rubberized Armor-Coated Tongue and Bumpers
Automotive Grade Undercoating
Painted Roof Bows
5' Wedge Flat Nose w/ 64" Ramp Door
Tube Main Rails
24" On-Center Floor Crossmembers
24" On- Center Wall Posts and Tube Roof Bows
Rear Ramp Door w/ Flap
(9) Flush-Mount D-Rings (Shipped Loose)
36" Solid RV Side Door
Plastic Door Holdbacks
3/4" High-Performance Floor
12" Tall 3/4" Kickplate

2 - 5/16" Coupler

6mm Plywood Walls w/ 6mm Plywood Trim **One-Piece Aluminum Roof** .030 Exterior Metal Screwed Exterior w/ Color Matching Screws where available 24" Tall .045 Stoneguard .063 Smooth Fenders 3" Aluminum Top-Rail Trim 1 - 1/2" Aluminum Bottom Trim 7-Way Connector on TA Models Breakaway Battery, Box, and Switch **All LED Lighting** (1) LED Sidewall Mounted Dome Light (2) LED Dome lights w/ Switch on 7' Wides (14' or longer) and 8.5' Wides 3-Year Limited Warranty

## 2500 Upgrades (Standard on 8.5' Wide Models)

16" On-Center Floor Crossmembers 16" On-Center Wall Posts 36" Solid RV Door Aluminum Door Holdbacks 3/8" Plywood Walls w/ 3/8" Plywood Trim 3" Aluminum Bottom Rail Semi-Screwless Screws on Seams (2) LED Dome Lights w/ Switch

DARKHORSE. THE WINNING BET!





		. W	Hitch Weight**	GVWR	Weights	Brakes	Axle Type	Axles	Vheel Bo	Load Range	Tire Size	Hitch Ball Size	Top of Hitch Ball	√itch, Ti	)ist. Betv	Rear Ope	Rear Ope	Platform Height	nterior Height	Interior Width	Interior Length <sup>1</sup>	Overall Height	Overall Width	Overall Length	Dimensions	
*With Beaver Tail	Curb Weight**		ght**						Wheel Bolt Pattern	ge		Size	ch Ball	Hitch, Tires, Axles	Dist. Between Cables	Rear Opening Width	Rear Opening Height*	Height	eight	/idth	ength <sup>1</sup>	eight	idth	ngth	ons	
**Approximate Weights	2,760 lbs.	2 760 lbc	415 lbs.	7,000 lbs.		Electric	4" Drop	Tandem	5-Bolt/4.5	С	ST205/ 75R15	2 5/16"	19"		81"	82"	75"	20"	78"	86"	18.5'	101"	102"	20'		7.5x19 TA35
Weights	2,930 lbs.	3 0 30 lbs	440 lbs.	7,000 lbs.		Electric	4" Drop	Tandem	5-Bolt/4.5	С	ST205/ 75R15	<b>2</b> 5/16"	19"		81"	82"	75"	20"	78"	86"	20.5'	101"	102"	22'		7.5x21 TA35
3,900 lbs.	3,100 lbs.	3 100 lbs	465 lbs.	7,000 lbs.		Electric	4" Drop	Tandem	5-Bolt/4.5	C	ST205/ 75R15	2 5/16"	19"		81"	82"	75"	20"	78" 78" 78"	86"	22.5'	101"	102"	24'		7.5x23 TA35
J,/J0 103.	3,2/0 lbs.	2 270 lbc	490 lbs.	7,000 lbs.		Electric	4" Drop	Tandem	5-Bolt/4.5	С	ST205/ 75R15	2 5/16"	19"		81"	82"	75"	20"		86"	24.5'	101"	102"	26'		7.5x25 TA35
6,430 lbs.	3,540 lbs.	3 E 40 lbs	530 lbs.	9,990 lbs.		Electric	4" Drop	Tandem	6-Bolt/5.5	D	ST225/ 75R15	2 5/16"	20"		81"	82"	75"	21"		86"	26.5'	102"	102"	28'		7.5x27 TA52
Specs, based on	3,440 lbs.	3 440 lbc	515 lbs.	7,000 lbs.		Electric	4" Drop	Tandem	5-Bolt/4.5	C	ST205/ 75R15	25/16"	19"		91"	92"	75"	20"	78"	96"	20.5'	101"	102"	22'		8.5x21 TA35
sed on 1500	3,/10 lbs.	3 710 lbs	555 lbs.	7,000 lbs.		Electric	4" Drop	Tandem	5-Bolt/4.5	С	ST205/ 75R15	25/16"	19"		91"	92"	75"	20"	78"	96"	22.5'	101"	102"	24'		8.5x23 TA35
Series   Spe	3,880 lbs.	3 000 %	580 lbs.	9,990 lbs.		Electric	4" Drop	Tandem	6-Bolt/5.5	D	ST225/ 75R15	2 5/16"	20"		91"	92"	75"	21"	78"	96"	24.5'	102"	102"	26'		8.5x25 TA52
ecs. are subje	4,050 lbs.	4 0E0 lbs	605 lbs.	9,990 lbs.		Electric	4" Drop	Tandem	6-Bolt/5.5	D	ST225/ 75R15	2 5/16"	20"		91"	92"	75"	21"	78"	96"	26.5'	102"	102"	28'		8.5x27 TA52
ect to change	4,220 lbs.	4 220 lbs	630 lbs.	9,990 lbs.		Electric	4" Drop	Tandem	6-Bolt/5.5	D	ST225/ 75R15	2 5/16"	20"		91"	92"	75"	21"	78"	96"	28.5'	102"	102"	30'		8.5x29 TA52
1500 Series   Specs. are subject to change without notice.	4,390 lbs	4 300 lbs	660 lbs.	9,990 lbs.		Electric	4" Drop	Tandem	6-Bolt/5.5	D	ST225/ 75R15	2 5/16"	20"		91"	92"	75"	21"	78"	96"	30.5′	102"	102"	32'		8.5x31 TA52

## **METAL COLORS**

Trailer Black

Victory Red

Polar White

**METALLIC FINISH** 

Light Pewter Silver Mist

Indigo Blue

Charcoal



Office: (269) 464-2620 Fax: (269) 464-2621 500 S Miller Drive White Pigeon, MI 49099