## **MULE PRO-MX™ EPS**





MSRP **\$12,899** 

**BRIGHT WHITE** 



TIMBERLINE GREEN



## **POWER**

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 35.7 amp

(max)

Park Brake Type Independent, Mechanical Disc

**Ground Clearance** 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed 33.4 x 44.1 x 9.1 in

Dimensions (LxWxH)

**Cargo Bed Load** 

Capacity

Payload Capacity 1200 lb

Seating Capacity 2

Towing Capacity 1500 lb

Lighting (2) Halogen headlights. (2) LED headlights

699 lb (600 lb California models)

## **CAPABILITY**

Front Suspension / Double wishbone / 8.6 in Wheel Travel

Rear Suspension / Wheel Travel Double wishbone/9.1 in

Front Tires 25x8.00-12, radial
Rear Tires 25x10.00-12, radial

Steering Electric Power Steering (EPS), Tilt steering

Front Brakes Dual Disc, 2 piston caliper
Rear Brakes Dual Disc, 1 piston caliper

## **DETAILS**

Overall Length 110.0 in
Overall Width 60.0 in
Overall Height 74.4 in

Curb Weight 1587.6 lb\*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer,

fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps

Wheel Type Steel

Color Choices Timberline Green, Bright White

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.