

tow DOLLIES



Standard Features

- We use easy-lube hubs which ease the re-packing of wheel bearings by eliminating the need for disassembly, and are backed by a 1-year warranty.
- All of our dollies are equipped with new tires and wheels that are computer balanced to assure a smooth ride at all towing speeds.
- Our ramps and carrying pan tilt rearward for loading and feature a raised tread grip pattern that gives extra traction making the Tilt-Bed Loading safer and easier.
- Our fenders are molded of ¼" thick polyethylene which eliminates metal fatigue problems common with steel fenders, and they will not scratch or rust. They feature oval waterproof lights that are mounted with an exclusive light retainer system to insure their secure attachment.
- The carrying pan steers for your car by swiveling smoothly on polyethylene pads which are maintenance free.
- Both safety chains have a unique s-hook safety closure added to insure their secure attachment to the tow vehicle at all times.
- A factory molded plug-together wiring harness is used to eliminate the need for wire splices which often corrode and lead to wiring shorts. It is also poly loomed where exposed and carefully routed outside the fender well to prevent wires from being damaged by debris thrown up from the tire.
- We use an exclusive painting process which involves chemically cleansing and etching the bare metal before applying a durable powder coat finish. This extra effort makes our dollies finish look better and last longer.
- 10,000 pound rated ratchets and adjustable straps securely fasten most 13" through 16" tires and wheels.
- Every Master Tow dolly is backed by a 1-year written warranty to show our commitment to quality.

2 models available to meet all your towing needs

Model 77T
For towing small to
mid-size cars
(towed vehicle tread width 40" - 77")

Model 80THD (Heavy Duty)
For towing small to
full-size cars, vans & trucks
(towed vehicle tread width 40" - 80")

MASTER TOW

Available Options



14" Radial Tire



Electric Brakes
Break Away Kit



Electric & Surge
Drum Brakes



LED Lights with
Lifetime Warranty

Available Accessories



Spare Tire &
Mount Kit



Towed Vehicle
Secure Chains



Bolt On Winch Kit



Magnetic Light Kit

Specifications

MODEL	77T	80THD
Towed Vehicle Tread Width (min-max)	40" - 77"	40" - 80"
Maximum Overall Width at Front Doors for Vehicle in Tow	75"	78"
Overall Width	99"	102"
Overall Length	121.5"	121.5"
Height at Fender	26"	26"
Ground Clearance	6"	6"
Gross Vehicle Weight Rating	3,000 lbs.	3,500 lbs.
Empty Weight	450 lbs.	550 lbs.
Actual Cargo Capacity	2,550 lbs.	2,950 lbs.
Maximum Gross Weight of Vehicle to be Towed	4,250 lbs.	4,900 lbs.
Tire Size	ST 205/75 14" 6 Ply Rated	ST 205/75 14" 6 Ply Rated
Coupler Size	2"	2"
Coupler Class	SAE 3/5,000 lbs.	SAE 3/5,000 lbs.

CONTACT:



MASTER TOW

783 Slocomb Road
Fayetteville, NC 28311
(910) 630-2000 • 1-800-522-2190
Fax (910) 630-2016
Email: mastertow@mastertow.com
Web: www.mastertow.com